

Jarrah Flooring

Jarrah is a high density and extremely hardwearing hardwood, which ranges in colours from dark pink to deep reddish browns. With an even texture and interlocking grain, Jarrah reflects light to give great lustre and depth to its appearance, while highlighting the natural characteristics.

A Jarrah Floor is the perfect choice to complement any interior space and will provide many years of lasting beauty.


The colour range of Jarrah Flooring complements iron and steel, and works well alongside granite and glass, making it ideal for both classic and contemporary interiors. A hardwearing Jarrah Floor is sure to remain a centrepiece in your home for generations.

A suitable coating can be applied to enhance the grain and protect the floor, making it easier to maintain.

Jarrah Flooring will not collect dust or conceal dirt, making it a natural choice for asthma and hay fever sufferers.

Technical Information

Species	E.marginata
Common Name	Jarrah
Origin	Found only on lateritic soils in the southwest of Western Australia
Colour	Light Pink to reddish brown
Workability	Relatively easy to work with common woodworking tools
Durability class	Class 2 Jarrah is a highly durable hardwood with natural flame – resistant properties . When used in exterior applications it exhibits excellent termite and rot resistance.
Hardness	8.5kN
Kiln Dried Density	About 820kg/m ³
Strength Group	54
Modulus of Rupture	112MPa
Modulus of Elasticity	13,000MPa
Maximum Crushing Strength	61MPa
Grades	Prime and Standard
Sizes	80x19 Tongue and Grooved Secret Nailed End Matched 85x13 Tongue and Grooved Overlay 105x13 Tongue and Grooved Overlay 130x19 Tongue and Grooved Secret Nailed End Matched



The Sustainable Resource

Auswest Timbers is supplied with logs harvested and sourced from sustainably managed forests by the Western Australian Government's agency, the Forest Products Commission.

The Forest Products Commission has implemented an environmental management system that has been certified as complying with the requirements of the international standard AS/NZS ISO 14001 and in January 2009 achieved certification to the Australian Forestry Standard (AFS).

For more information about the AFS, please visit www.forestrystandard.org.au.

To further assure our customers that all timber supplied from grower to manufacturer is sustainably managed, Auswest Timbers achieved Chain of Custody certification in April 2012.



Storage, Installation & Care

Auswest Timbers' Jarrah Flooring is wrapped in plastic to protect against moisture damage during transport and storage. Jarrah Flooring is a natural product that expands and contracts with seasonal changes. As timber can be affected by the moisture content of the air, it is important to acclimatise your floor to the local climate prior to installation.

The plastic wrapping should be removed and each board should be exposed to the air conditions in the environment in which it will be installed. The time taken for the flooring to acclimatise varies, but Auswest Timbers recommends that it should be suitably acclimatised before installation.

Adequate sub-floor ventilation is essential for the successful performance of a solid hardwood floor. If humidity remains high beneath the floor, the boards will absorb the moisture and expand. Excessive humidity in the under-floor area may be caused by a lack of sufficient cross-ventilation or from damp soil conditions arising from inadequate drainage. These conditions lead to swelling of the flooring and can lead to an eventual decay. This can create an unhealthy mustiness within the house, so it is very important to ensure adequate sub-floor ventilation to reduce expansion and cupping of hardwood floors.

It is recommended that hardwood floors be laid by a professional with knowledge and experience in all aspects of hardwood flooring installation, sanding and polishing.

Once the floor has been laid, a number of changes in the climate may occur and determine the degree of movement of the Jarrah Flooring. These include large expanses of glass, fireplaces, fridges, air conditioners and any appliances that vent warm air. If you wish to minimise movement, you must minimise the changes in the climatic conditions that occur.

You must also avoid exposure of the Jarrah Floor to direct sunlight, heat or excessive moisture (such as excessive wet mopping).



Auswest Timbers



Contact Us

To find out more about Auswest Timbers and its products, please contact us.

Email sales@auswesttimber.com.au
www.auswesttimber.com.au

Welshpool Trade & Retail Centre
455 Orrong Road, Welshpool
Western Australia 6106

Ph +61 8 9351 6429
Fax +61 8 9351 6407

Auswest Timbers Pty Ltd
Head Office, Western Australia

Ph +61 8 9351 6452
Fax +61 8 9351 6450